



Datasheet

Splash LED Damp-proof diffuser luminaire

1005.3389

810.AB.50JA.0



System power	49 W
Source of light	LED (Light Emitting Diode)
Colour temperature	4000 K
Luminaire flux	5850 lm
Ingress Protection	IP66
Colour Rendering Index	CRI >80
UGR C0 4H/8H	25.4
UGR C90 4H/8H	20.6
Economic life-time	L90 (B50) 50'000h
Light control	ON/OFF
Finish	dark grey
Weight	3.3 kg

Damp-proof diffuser luminaire Splash LED for surface, wall and pendant mounting, with LED (Light Emitting Diode), system power: 49 W, luminous flux of luminaire 5850 lm, CRI >80, 4000 K, neutral white, SDCM 3, L90 (B50) 50'000h, 230 V, direct light emission, wide beam, 1 integral control gear, ON/OFF, housing in acrylonitrile butadiene styrene (ABS), dark grey and diffuser in polymethyl methacrylate (PMMA), transparent, with plastic clamps, Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0291), luminaire complies with the strict requirements for Minergie-certified luminaires (96 lm/W)

protection class I, ingress protection IP66, glow wire test 650 °C, impact strength: IK 06, service temperature range -20°C to +40°C, L = 1572 mm, B = 95 mm, H = 100 mm