




Datasheet

Splash Clear LED Damp-proof diffuser luminaire

1005.3420

810.CB.40JA.0



System power	35 W
Source of light	LED (Light Emitting Diode)
Colour temperature	4000 K
Luminaire flux	4300 lm
Ingress Protection	IP66
Colour Rendering Index	CRI >80
UGR C0 4H/8H	25.1
UGR C90 4H/8H	20.1
Economic life-time	L90 (B50) 50'000h
Light control	ON/OFF
Weight	2.576 kg

Damp-proof diffuser luminaire Splash Clear LED for surface, wall and pendant mounting, with LED (Light Emitting Diode), system power: 35 W, luminous flux of luminaire 4300 lm, CRI >80, 4000 K, neutral white, SDCM 3, L90 (B50) 50'000h, 230 V, direct-indirect light emission, wide beam, 1 integral control gear, ON/OFF, housing in polycarbonate (PC), and diffuser in polycarbonate (PC), transparent, with chrome steel clamps, Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0292), luminaire complies with the strict requirements for Minergie-certified luminaires (96 lm/W)

protection class I, ingress protection IP66, glow wire test 850 °C, impact strength: IK 10, service temperature range -20°C to +40°C, L = 1272 mm, B = 95 mm, H = 100 mm