



## Datasheet

### Flow LED Surface-mounted luminaire

1005.8481

84W01L1227DC0



<b>System power</b>	20 W
<b>Source of light</b>	LED (Light Emitting Diode)
<b>Colour temperature</b>	3000 K
<b>Luminaire flux</b>	1960 lm
<b>Ingress Protection</b>	IP44
<b>Colour Rendering Index</b>	CRI >80
<b>UGR C0 4H/8H</b>	20.1
<b>UGR C90 4H/8H</b>	17.9
<b>Economic life-time</b>	L80 (B10) 50'000h
<b>Light control</b>	DALI
<b>Finish</b>	natural-colour anodised
<b>Weight</b>	2.262 kg

Ceiling and wall mounted luminaire Flow LED HPE (High Performance Efficiency), with LED (Light Emitting Diode), system power: 20 W, luminous flux of luminaire 1960 lm, CRI >80, 3000 K, warm white, SDCM 3, L80 (B10) 50'000h, 230 V, direct light emission, support in aluminium, natural-colour anodised, diffuser in polycarbonate (PC) satin blend white, SLA Technology (Spread Light Applicator), 1 integral control gear, DALI, Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0275), luminaire complies with the strict requirements for Minergie-certified luminaires (90 lm/W)

protection class I, ingress protection IP44, glow wire test 850 °C, impact strength: IK 07

L = 1190 mm, B = 54 mm, H = 80 mm