



Datasheet

Flow LED Surface-mounted luminaire

1005.8494

84W01L1532DC0



System power	25 W	<p>Ceiling and wall mounted luminaire Flow LED HPE (High Performance Efficiency), with LED (Light Emitting Diode), system power: 25 W, luminous flux of luminaire 2450 lm, CRI >80, 3000 K, warm white, SDCM 3, L80 (B10) 50'000h, 230 V, direct light emission, support in aluminium, natural-colour anodised, diffuser in polycarbonate (PC) satin blend white, SLA Technology (Spread Light Applicator), 1 integral control gear, DALI, Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0275), luminaire complies with the strict requirements for Minergie-certified luminaires (90 lm/W)</p> <p>protection class I, ingress protection IP44, glow wire test 850 °C, impact strength: IK 07</p> <p>L = 1490 mm, B = 54 mm, H = 80 mm</p>
Source of light	LED (Light Emitting Diode)	
Colour temperature	3000 K	
Luminaire flux	2450 lm	
Ingress Protection	IP44	
Colour Rendering Index	CRI >80	
UGR C0 4H/8H	20.1	
UGR C90 4H/8H	17.9	
Economic life-time	L80 (B10) 50'000h	
Light control	DALI	
Finish	natural-colour anodised	
Weight	2.84 kg	