



## Datasheet

### Channel S Up C-LED Pendant luminaire 2001.0719



<b>System power</b>	47 W	Pendant luminaire Channel S Up C-LED with LED (Light Emitting Diode), system power: 47 W, luminous flux of luminaire 4500 lm, CRI >80, 4000 K, neutral white, SDCM 3, L80 (B10) 50'000h, max. 3000 cd/m <sup>2</sup> , 230 V, direct-indirect light emission, housing in aluminium, natural-colour anodised, diffuser in polycarbonate (PC) satin, micro-prismatic CLD (Controlled Luminance Diffuser), 1 integral control gear, DALI, with halogen-free wiring,
<b>Source of light</b>	LED (Light Emitting Diode)	
<b>Colour temperature</b>	4000 K	
<b>Luminaire flux</b>	4500 lm	
<b>Ingress Protection</b>	IP20	
<b>Colour Rendering Index</b>	CRI >80	
<b>UGR C0 4H/8H</b>	13.2	
<b>UGR C90 4H/8H</b>	13.5	
<b>Economic life-time</b>	L80 (B10) 50'000h	
<b>Light control</b>	DALI	
<b>Finish</b>	natural-colour anodised	protection class I, ingress protection IP20, glow wire test 650 °C, impact strength: IK 08, service temperature range -5°C to +30°C, L = 1250 mm, B = 65 mm, H = 71 mm, p = 1500 mm
<b>Weight</b>	3.18 kg	