



Datasheet

Isigo 2 Ceiling and wall mounted luminaire

2008.3700

ISIGO2 RND CW250 LED1500-840 MLMC WH ONF



| | | |
|---------------------------|------------------|--|
| System power | 12 W | <p>Ceiling and wall mounted luminaire Isigo 2 with LED, system power: 8 / 12 W, standby power 0 W, Multilumen 1000/1500 lm, colour rendering index CRI > 80, colour temperature can be set directly on the luminaire 2700/3000/4000 K, warm to neutral white, lifetime LED L80 50'000 h, colour tolerances SDCM 3, photobiological safety: the luminaire poses no danger (RG0), 230 V, direct light emission, housing in polycarbonate (PC), white, RAL 9016, with opal diffuser, 110°, 1 integral control gear, ON/OFF,</p> <p>protection class II, ingress protection IP54, glow wire test 650 °C, impact strength: IK 10, this product contains a light source of energy efficiency class B and EPREL registration number: 1451558 $\varnothing = 250$ mm, H = 55 mm</p> |
| Luminaire flux | 1500 lm | |
| Multilumen | 1000/1500 lm | |
| Colour temperature | 4000 K | |
| Multicolor | 2700/3000/4000 K | |
| CRI | CRI > 80 | |
| UGR C0 4H/8H | 23 | |
| UGR C90 4H/8H | 24 | |
| Economic life-time | L80 50'000 h | |
| Light control | ON/OFF | |
| Ingress Protection | IP54 | |
| Finish | white | |
| Weight | 0.9 kg | |