



Datasheet

Beam Office Uplight

2010.5069

BEAM 410 LED9700-840 NB BK CAS



| | |
|---------------------------|----------------|
| System power | 65 W |
| Luminaire flux | 9700 lm |
| Colour temperature | 4000 K |
| CRI | CRI > 80 |
| UGR C0 4H/8H | 10 |
| UGR C90 4H/8H | 10 |
| Economic life-time | L80 50'000 h |
| Light control | Casambi |
| Ingress Protection | IP20 |
| Finish | black anodised |
| Weight | 4.500 kg |

Uplight Beam Office with LED, system power: 65 W, standby power 0.5 W, luminous flux of luminaire 9700 lm, colour rendering index CRI > 80, 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, office-compatible and glare-free according to EN 12464-1 (UGR < 19; Lmax ≥ 65° ≤ 3000 cd/m²), photobiological safety: the luminaire poses no danger (RG0), 230 V, nominal current: 0.29 A, indirect light emission, narrow beam, with pushbutton on the housing, in aluminium, black, similar to RAL 9005, anodised, 1 integral control gear, Casambi, dimmable 0-100 %, 2m power supply cable with plug, with USB-C PD 2x25W,

protection class II, ingress protection IP20, glow wire test 650 °C, this product contains a light source of energy efficiency class D and EPREL registration number: 865219
 Ø = 100 mm, total height = 410 mm