



Datasheet

Flow LED Surface-mounted luminaire

1005.8466

84W01L0916DC0



System power	16 W
Source of light	LED (Light Emitting Diode)
Colour temperature	3000 K
Luminaire flux	1500 lm
Ingress Protection	IP44
Colour Rendering Index	CRI >80
UGR C0 4H/8H	20.2
UGR C90 4H/8H	17.8
Economic life-time	L80 (B10) 50'000h
Light control	DALI
Finish	natural-colour anodised
Weight	1.92 kg

Ceiling and wall mounted luminaire Flow LED HPE (High Performance Efficiency), with LED (Light Emitting Diode), system power: 16 W, luminous flux of luminaire 1500 lm, CRI >80, 3000 K, warm white, SDCM 3, L80 (B10) 50'000h, 230 V, direct light emission, support in aluminium, natural-colour anodised, diffuser in polycarbonate (PC) satin blend white, SLA Technology (Spread Light Applicator), 1 integral control gear, DALI, Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0275), luminaire complies with the strict requirements for Minergie-certified luminaires (90 lm/W)

protection class I, ingress protection IP44, glow wire test 850 °C, impact strength: IK 07
 L = 905 mm, B = 54 mm, H = 80 mm