



## Datasheet

### Solo Slim Office C-LED Ceiling mounted luminaire

1021.7105  
114H296L2JC



<b>System power</b>	46 W	<p>Ceiling mounted luminaire Solo Slim Office C-LED with LED (Light Emitting Diode), system power: 46 W, luminous flux of luminaire 5800 lm, CRI &gt;80, 4000 K, neutral white, SDCM 3, L80 (B10) 50'000h, max. 3000 cd/m<sup>2</sup>, 230 V, direct-indirect light emission, frame in aluminium, silver, neat shadow gap, diffuser in polymethyl methacrylate (PMMA) micro-prismatic CLD (Controlled Luminance Diffuser), 1 integral control gear, DALI, Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0282), luminaire complies with the strict requirements for Minergie-certified luminaires (96 lm/W)</p> <p>protection class I, ingress protection IP40, glow wire test 650 °C, impact strength: IK 07 Ø = 680 mm, H = 81 mm</p>
<b>Source of light</b>	LED (Light Emitting Diode)	
<b>Colour temperature</b>	4000 K	
<b>Luminaire flux</b>	5800 lm	
<b>Ingress Protection</b>	IP40	
<b>Colour Rendering Index</b>	CRI >80	
<b>UGR C0 4H/8H</b>	17.7	
<b>UGR C90 4H/8H</b>	17.6	
<b>Economic life-time</b>	L80 (B10) 50'000h	
<b>Light control</b>	DALI	
<b>Finish</b>	silver	
<b>Weight</b>	8.078 kg	