



## Datasheet

### Isigo Ceiling and wall mounted luminaire

2002.3828

ISIGO RND CW300 LED2500-840 WH ONF MSEN



|                               |                            |
|-------------------------------|----------------------------|
| <b>System power</b>           | 25 W                       |
| <b>Source of light</b>        | LED (Light Emitting Diode) |
| <b>Colour temperature</b>     | 4000 K                     |
| <b>Luminaire flux</b>         | 2500 lm                    |
| <b>Colour Rendering Index</b> | CRI >85                    |
| <b>UGR C0 4H/8H</b>           | 24                         |
| <b>UGR C90 4H/8H</b>          | 24                         |
| <b>Economic life-time</b>     | L80 50'000 h               |
| <b>Light control</b>          | ON/OFF                     |
| <b>Ingress Protection</b>     | IP54                       |
| <b>Finish</b>                 | white                      |
| <b>Weight</b>                 | 1.6 kg                     |

Ceiling and wall mounted luminaire Isigo with LED (Light Emitting Diode), system power: 25 W, luminous flux of luminaire 2500 lm, CRI >85, 4000 K, neutral white, SDCM 3, L80 50'000 h, 230 V, direct light emission, housing in polycarbonate (PC), white, RAL 9016, with opal diffuser, 110 °, 1 integral control gear, ON/OFF, with invisibly integrated HF-based motion detector, detection through objects possible, Colour temperature 3000K or 4000K can be set directly on the luminaire

protection class II, ingress protection IP54, glow wire test 850 °C, impact strength: IK 10  
 Ø = 300 mm, H = 55 mm

## Datasheet: Accessories

### Isigo Ceiling and wall mounted luminaire

2002.3828

ISIGO RND CW300 LED2500-840 WH ONF MSEN



**2002.6229**

Remote control

Remote control Isigo