



# Datasheet

## Cosmos 2 Recessed directional spotlight

2010.1236

COSMOS2 DS CR75 LED810-930 36 WH ONF



<b>System power</b>	12 W
<b>Luminaire flux</b>	810 lm
<b>Colour temperature</b>	3000 K
<b>CRI</b>	CRI > 92
<b>UGR C0 4H/8H</b>	21
<b>UGR C90 4H/8H</b>	21
<b>Economic life-time</b>	L70 50'000 h
<b>Light control</b>	ON/OFF
<b>Ingress Protection</b>	IP20
<b>Finish</b>	white
<b>Weight</b>	0.325 kg

Recessed directional spotlight Cosmos 2 with LED, system power: 12 W, luminous flux of luminaire 810 lm, colour rendering index CRI > 92, colour temperature 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L70 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, direct light emission, housing in aluminium, with ceiling trim, white, medium wide beam, 36°, operating unit included in delivery, ON/OFF, dimmable with leading-edge control or trailing edge phase,

protection class II, ingress protection IP20, glow wire test 850 °C, Ø = 90 mm, DAØ = 75 mm, ET = 100 mm, swivelling 90°