



Datasheet

Beam Office Uplight

2010.5066

BEAM 410 LED9200-830 NB BK CAS



System power	65 W
Luminaire flux	9200 lm
Colour temperature	3000 K
CRI	CRI > 80
UGR C0 4H/8H	10
UGR C90 4H/8H	10
Economic life-time	L80 50'000 h
Light control	Casambi
Ingress Protection	IP20
Finish	black anodised
Weight	4.595 kg

Uplight Beam Office with LED, system power: 65 W, standby power 0.5 W, luminous flux of luminaire 9200 lm, colour rendering index CRI > 80, 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, office-compatible and glare-free according to EN 12464-1 (UGR < 19; L_{max} ≥ 65° ≤ 3000 cd/m²), photobiological safety: the luminaire poses no danger (RG0), 230 V, nominal current: 0.29 A, indirect light emission, narrow beam, with pushbutton on the housing, in aluminium, black, similar to RAL 9005, anodised, 1 integral control gear, Casambi, dimmable 0-100 %, 2m power supply cable with plug, with USB-C PD 2x25W,

protection class II, ingress protection IP20, glow wire test 650 °C, this product contains a light source of energy efficiency class D and EPREL registration number: 865226
 Ø = 100 mm, total height = 410 mm