



# Preliminary Datasheet

## Beam Office Uplight

2011.1099

Available as of 22.04.2024

BEAM 410 LED7500-927 NB WH CAS



<b>System power</b>	65 W
<b>Luminaire flux</b>	7500 lm
<b>Colour temperature</b>	2700 K
<b>CRI</b>	CRI > 90
<b>UGR C0 4H/8H</b>	10
<b>UGR C90 4H/8H</b>	10
<b>Economic life-time</b>	L80 50'000 h
<b>Light control</b>	Casambi
<b>Ingress Protection</b>	IP20
<b>Finish</b>	white
<b>Weight</b>	4.495 kg

Uplight Beam Office with LED, system power: 65 W, standby power 0.5 W, luminous flux of luminaire 7500 lm, colour rendering index CRI > 90, 2700 K, warm white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, office-compatible and glare-free according to EN 12464-1 (UGR < 19; Lmax ≥ 65° ≤ 3000 cd/m²), photobiological safety: the luminaire poses no danger (RG0), 230 V, indirect light emission, narrow beam, with pushbutton on the housing, in aluminium, white, RAL 9003, 1 integral control gear, Casambi, dimmable 0-100 %, 2m power supply cable with plug,

protection class II, ingress protection IP20, glow wire test 650 °C, Ø = 100 mm, total height = 410 mm