




Datasheet

Echo 137 LED Recessed downlight

1001.2475

24W1F18JC.00



| | |
|-------------------------------|----------------------------|
| System power | 14 W |
| Source of light | LED (Light Emitting Diode) |
| Colour temperature | 4000 K |
| Luminaire flux | 1150 lm |
| Ingress Protection | IP20 / IP44 |
| Colour Rendering Index | CRI >90 |
| UGR C0 4H/8H | 22.7 |
| UGR C90 4H/8H | 22.7 |
| Economic life-time | L80 (B50) 50'000h |
| Light control | DALI |
| Finish | white |
| Weight | 1.066 kg |

Recessed downlight Echo 137 LED with LED (Light Emitting Diode), system power: 14 W, luminous flux of luminaire 1150 lm, standby power 0.4 W, CRI >90, 4000 K, neutral white, SDCM 3, L80 (B50) 50'000h, 230 V, direct light emission, housing in aluminium, with ceiling trim, white, with white reflector, (F), wide beam, 80 °, operating unit included in delivery, DALI,

protection class I, ingress protection IP20 / IP44, glow wire test 850 °C, impact strength: IK 08
 $\varnothing = 152 \text{ mm}$, $DA\varnothing = 137 \text{ mm}$, $ET = 100 \text{ mm}$