




# Datasheet

## Viva LED Recessed downlight

1001.6979

3304W.D12DA00



<b>System power</b>	15 W	<p>Recessed downlight Viva LED with LED (Light Emitting Diode), system power: 15 W, luminous flux of luminaire 1520 lm, CRI &gt;80, 3000 K, warm white, SDCM 3, L70 (B50) 50'000h, 230 V, direct light emission, housing in aluminium, with ceiling trim, white, wide beam, 105 °, operating unit included in delivery, ON/OFF,</p> <p>protection class I, ingress protection IP20 / IP44, glow wire test 650 °C, impact strength: IK 08  <math>\varnothing = 175 \text{ mm}</math>, <math>DA\varnothing = 155 \text{ mm}</math>, <math>ET = 85 \text{ mm}</math></p>
<b>Source of light</b>	LED (Light Emitting Diode)	
<b>Colour temperature</b>	3000 K	
<b>Luminaire flux</b>	1520 lm	
<b>Ingress Protection</b>	IP20 / IP44	
<b>Colour Rendering Index</b>	CRI >80	
<b>UGR C0 4H/8H</b>	28.2	
<b>UGR C90 4H/8H</b>	28.2	
<b>Economic life-time</b>	L70 (B50) 50'000h	
<b>Light control</b>	ON/OFF	
<b>Finish</b>	white	
<b>Weight</b>	0.914 kg	