



## Datasheet

### Novo Round LED Recessed downlight

2002.3785



<b>System power</b>	19 W	<p>Recessed downlight Novo Round LED inner ring set back, with LED (Light Emitting Diode), system power: 19 W, luminous flux of luminaire 1500 lm, CRI &gt;90, 4000 K, neutral white, SDCM 3, L80 (B50) 50'000h, RG 1 - low risk, 230 V, 500 mA, direct light emission, housing in die-cast aluminium, with ceiling trim, white, RAL 9016, with reflector, 35 °, operating unit included in delivery, ON/OFF,</p> <p>protection class II, ingress protection IP20 / IP44, glow wire test 650 °C, impact strength: IK 01</p> <p>Ø = 118 mm, DAØ = 100 mm - 113 mm, ET = 104 mm</p>
<b>Source of light</b>	LED (Light Emitting Diode)	
<b>Colour temperature</b>	4000 K	
<b>Luminaire flux</b>	1500 lm	
<b>Ingress Protection</b>	IP20 / IP44	
<b>Colour Rendering Index</b>	CRI >90	
<b>UGR C0 4H/8H</b>	15.6	
<b>UGR C90 4H/8H</b>	15.6	
<b>Economic life-time</b>	L80 (B50) 50'000h	
<b>Light control</b>	ON/OFF	
<b>Finish</b>	white	
<b>Weight</b>	0.54 kg	