



Datasheet

Isigo 2 Ceiling and wall mounted luminaire

2008.3702

ISIGO2 RND CW250 LED1500-840 MLMC WH ONF MSEN



System power	12 W	<p>Ceiling and wall mounted luminaire Isigo 2 with LED, system power: 8 / 12 W, standby power 0 W, Multilumen 1000/1500 lm, colour rendering index CRI > 80, colour temperature can be set directly on the luminaire 2700/3000/4000 K, warm to neutral white, lifetime LED L80 50'000 h, colour tolerances SDCM 3, photobiological safety: the luminaire poses no danger (RG0), 230 V, direct light emission, housing in polycarbonate (PC), white, RAL 9016, with opal diffuser, 110°, 1 integral control gear, ON/OFF, with invisibly integrated HF-based motion detector and daylight control, detection through objects possible,</p> <p>protection class II, ingress protection IP54, glow wire test 650 °C, impact strength: IK 10, this product contains a light source of energy efficiency class B and EPREL registration number: 1451558 $\varnothing = 250$ mm, H = 55 mm</p>
Luminaire flux	1500 lm	
Multilumen	1000/1500 lm	
Colour temperature	4000 K	
Multicolor	2700/3000/4000 K	
CRI	CRI > 80	
UGR C0 4H/8H	23	
UGR C90 4H/8H	24	
Economic life-time	L80 50'000 h	
Light control	ON/OFF	
Ingress Protection	IP54	
Finish	white	
Weight	0.9 kg	